

EA0404

Warden Intercom Point Firephone

Information Sheet

Description

The Tyco EA0404 Warden Intercom Point (WIP) is designed specifically for use in emergency warning systems. WIPs are used to communicate between floor wardens and the main emergency evacuation panel. When the handset is lifted, the Firephone automatically calls the emergency evacuation panel.

When the emergency evacuation panel calls the WIP, the call tone sounds through the speaker in the body of the phone. Lifting the handset automatically transfers from the phone body speaker to the handset speaker.

This model A2096 supersedes the A2095. It features an enlarged cable entry area to suit Radox® cable and enhanced cable termination. The EA0404 is SSL listed for use with Tyco QE90 and SimplexGrinnell QE90 EWIS panels and approved as compliant with AS2220.

The EA0404 comes packaged with wall mounting bracket.

Refer to EWIS panel manuals for wiring details.

Specifications

Call Tone	>80dB 1W/1m
Frequency Response	300Hz to 3kHz
Line Impedance	600 Ohm / 4.7k Ohm
Size	diameter 200mm
SSL ActivFire listing	afp524
Part Number	EA0404



Figure 1. EA0404 WIP Phone

For all sales and inquiries, contact:



www.tycosafetyproducts-anz.com

Tyco Safety Products, a division of Tyco Asia Pacific Pty Limited A.B.N. 78 003 905 093, reserve the right to alter specifications without notice, in line with Tyco's policy of continuing product improvement.